



THERMAL PROTECTION

GUIDE 3569

HEAT | WELDING

Welding glove in cow split leather in highest quality with cotton lining, fitted with cuff and an elastic at wrist. Suitable for tasks in hot environments, contact heat for up to 100 degrees, suitable for MIG and MAG welding. Seams of heat-resistant Kevlar thread.

| Part Number/Size | |
|------------------|----------------|
| 10H3569-8/S | 10H3569-11/XL |
| 10H3569-9/M | 10H3569-12/2XL |
| 10H3569-10/L | |

- ▶ Fully lined
- ▶ Cow split leather
- ▶ Kevlar seams
- ▶ Long cuff
- ▶ Sizes 8-12



Durability Dexterity

CE CE CATEGORY 2

EN 388:2016 4143X

EN 407:2004 41324X

EN 12477:2001 TYPE A

EN 21420:2020



SUITABLE FOR:

Aftermarket network | Metal fabrication & transformation | Machinery & equipments | Wood, pulp & paper | Utilities & services

PROTECTION AGAINST:

Abrasions | Scratchers | Blisters | Lacerations

PROTECTIVE FEATURES:

Kevlar Seams | Contact heat protection level 1 (100°C, EN 407)

ERGONOMIC FEATURES:

Regular fit | Long Safety Cuff

QUALITY FEATURES:

REACH compliant

COLORS:

Honey

OUTERSIDE RAW MATERIAL:

Cow Split leather | Cow Split leather | Cow Split leather

INNERSIDE RAW MATERIAL:

Cotton | Fully lined

TOTAL LENGTH:

34-38 cm

